

APC PACKAGING SPECS

16" -20" COIL ID, 52" MAX COIL OD, 23" MIN COIL OD.

MAX SKID HEIGHT IS 20". HEIGHT OF SKID TO COIL OD RATIO <0.75 (HS:OD<0.75).

NO MORE THAN 12 COILS ON A SKID.

3500 LB MAX SKID.

COIL MUST BE CENTERED ON THE SKID.

SKID CONSTRUCTION SOLID, FASTENED TOGETHER SECURELY, NO NAILS/SCREWS PROTRUDING.

SKIDS SYMMETRICAL AND UNIFORM IN WIDTH, LENGTH, AND DIAGONAL.

SKIDS NOT TO EXCEED 56" IN WIDTH, LENGTH OR DIAGONAL.

OUTSIDE BOARDS MUST EXTEND BEYOND THE COIL OD, SUPPORTING THE COIL ON 4 CORNERS.

SKID DIAGONAL MUST BE GREATER THAN THE COIL OD.

TWO STRINGERS PARALLEL AND 24" TO 36" APART, OUTSIDE DIMENSION.

4 BOARD MIN. ON SKID.

BOARDS EQUALLY SPACED ON THE SKID.

STOCK REEL PAYOFF – COUNTER CLOCKWISE.